

Technical Datasheet SW 12 H

- Primarily for cleaning jobs in workshops and industrial production
- In the medical sector for the cleaning of larger quantities of instruments
- Drain on the back, to be operated on the side



Elektrical Data:

- | | |
|---|-------------------------|
| ▪ Mains voltage / Variants: | 100-120 / 220-240 (Vac) |
| ▪ Ultrasonic Frequency: | 38 kHz |
| ▪ Power consumption total: | 1000 Watt |
| ▪ Ultrasonic power effective: | 200 Watt |
| ▪ Ultrasonic peak max. | 800 Watt |
| ▪ Heating power: | 800 Watt |
| ▪ Ultrasonic Intensity (W / cm ²) | 2,6 |

Mechanical Data:

- | | |
|--|--|
| ▪ Tank max volume (approx. litre): | 12.75 |
| ▪ Tank service volume (approx. litre): | 9.00 |
| ▪ Tank internal dimensions: | 300 x 240 x 200 (W x D x H / approx. mm) |
| ▪ Unit external dimension: | 365 x 278 x 321 (W x D x H / approx. mm) |
| ▪ Weight (approx. Kg): | 7.5 |
| ▪ Material Housing (Stainless steel): | V2A 1.4301 (AISI 304) |
| ▪ Material Tank (Stainless steel): | V2A 1.4301 (AISI 304) |
| ▪ Thickness Tank (approx. mm) | 0.8 |

Technical properties:

- | | |
|--------------------------|------|
| ▪ Number of transducer: | 4 |
| ▪ LED – Display: | X |
| ▪ Unit handles: | X |
| ▪ Drain Diameter (inch“) | 3/8“ |

Accessories:

- | | |
|--|-----------------|
| ▪ Basket internal dimensions (approx. mm): | 250 x 190 x 120 |
| ▪ Basket loading (approx. Kg): | 7.0 |
| ▪ Basket (order-no.) | 100 402 |