

Technical Datasheet SW 45 H

- The large 45 litre ultrasonic unit is perfect for the cleaning of large quantities of cleaning parts or of big-size components, e.g. for industrial cleaning.
- Powerful ultrasound
- Short heating-up period
- The height of this unit is larger, therefore the operating panel is mounted to the top for ergonomical operation
- Easy-maintenance arrangement of the generator
- Drain on the back, to be operated on the side



Elektrical Data:

- | | |
|---|---------------|
| ▪ Mains voltage / Variants: | 220-240 (Vac) |
| ▪ Ultrasonic Frequency: | 38 kHz |
| ▪ Power consumption total: | 2000 Watt |
| ▪ Ultrasonic power effective: | 400 Watt |
| ▪ Ultrasonic peak max. | 1600 Watt |
| ▪ Heating power: | 1600 Watt |
| ▪ Ultrasonic Intensity (W / cm ²) | 2,6 |

Mechanical Data:

- | | |
|--|--|
| ▪ Tank max volume (approx. litre): | 45.00 |
| ▪ Tank service volume (approx. litre): | 35.00 |
| ▪ Tank internal dimensions: | 500 x 300 x 300 (W x D x H / approx. mm) |
| ▪ Unit external dimension: | 615 x 370 x 467 (W x D x H / approx. mm) |
| ▪ Weight (approx. Kg): | 25.0 |
| ▪ Material Housing (Stainless steel): | V2A 1.4301 (AISI 304) |
| ▪ Material Tank (Stainless steel): | V2A 1.4571 (AISI 316) |
| ▪ Thickness Tank (approx. mm) | 2.0 |

Technical properties:

- | | |
|--------------------------|------|
| ▪ Number of transducer: | 8 |
| ▪ LED – Display: | X |
| ▪ Unit handles: | X |
| ▪ Drain Diameter (inch“) | 1/2“ |

Accessories:

- | | |
|--|-----------------|
| ▪ Basket internal dimensions (approx. mm): | 455 x 270 x 190 |
| ▪ Basket loading (approx. Kg): | 20.0 |
| ▪ Basket (order-no.) | 100 522 |