

Technical Datasheet SW 6 H

- larger basket dimensions and a deeper tank than SW3H for long instruments or a larger amount of tools or other cleaning items
- also available with cut-out cover and 1 litre glass beakers
- drain on the back, to be operated on the side



Elektrical Data:

- | | |
|---|-------------------------|
| ▪ Mains voltage / Variants: | 100-120 / 220-240 (Vac) |
| ▪ Ultrasonic Frequency: | 38 kHz |
| ▪ Power consumption total: | 550 Watt |
| ▪ Ultrasonic power effective: | 150 Watt |
| ▪ Ultrasonic peak max. | 600 Watt |
| ▪ Heating power: | 400 Watt |
| ▪ Ultrasonic Intensity (W / cm ²) | 2,6 |

Mechanical Data:

- | | |
|--|--|
| ▪ Tank max volume (approx. litre): | 5.75 |
| ▪ Tank service volume (approx. litre): | 4.3 |
| ▪ Tank internal dimensions: | 300 x 151 x 150 (W x D x H / approx. mm) |
| ▪ Unit external dimension: | 365 x 186 x 264 (W x D x H / approx. mm) |
| ▪ Weight (approx. Kg): | 5.1 |
| ▪ Material Housing (Stainless steel): | V2A 1.4301 (AISI 304) |
| ▪ Material Tank (Stainless steel): | V2A 1.4301 (AISI 304) |
| ▪ Thickness Tank (approx. mm) | 0.8 |

Technical properties:

- | | |
|--------------------------|------|
| ▪ Number of transducer: | 3 |
| ▪ LED – Display: | X |
| ▪ Unit handles: | X |
| ▪ Drain Diameter (inch“) | 3/8“ |

Accessories:

- | | |
|--|----------------|
| ▪ Basket internal dimensions (approx. mm): | 255 x 115 x 75 |
| ▪ Basket loading (approx. Kg): | 5.0 |
| ▪ Basket (order-no.) | 100 401 |
| ▪ Cover with holes for 2 beakers (order-no.) | 100 536 |
| ▪ Set: 2 beakers with cover, cover with 2 holes and rubber rings (order-no.) | -- |