

Coil Specification (at 20 °C)

Coil Sensitivity	Nominal Voltage (VDC)	Nominal Current (mA)	Coil Resistance ($\Omega \pm 10\%$)	Power Consumption (W)	Pull-In Voltage (VDC)	Drop-Out Voltage (VDC)	Maximum Allowable Voltage (VDC)
JE	3	66.7	45	Abt. 0.2	75% Maximum	5% Minimum	150%
	5	40.0	125				
	6	33.3	180				
	9	22.2	405				
	12	16.7	720				
	24	8.3	2,880				
	48	4.2	11,520				

Ordering Information

JE - 1 12 D M - G

Contact Material:

NII: AgNi
G: AgNi Gilded
O: AgNi Plated
N: AgSnO₂
S: AgSnO₂ Gilded

Contact Form:

NII: One Form C
M: One Form A

Coil Type:

D: Standard DC Coil

Coil Voltage: 03: 3V, 05: 5V, 06: 6V, 09: 9V, 12: 12V, 24: 24V, 48: 48V

Number of Pole:

1: One Pole

Type:




JE

Classification


Model	JE	
Coil Sensitivity	Standard DC Coil	
Contact Form	1C	1A
Plastic Sealed Type	JE - 1 <input type="checkbox"/> <input type="checkbox"/> D - <input type="checkbox"/>	JE - 1 <input type="checkbox"/> <input type="checkbox"/> DM - <input type="checkbox"/>

Dimension

JE-D






BOTTOM VIEW




BOTTOM VIEW

JE-DM



BOTTOM VIEW



BOTTOM VIEW